



The Clear Choice
Water Filtration Systems



www.aquafilter.com



ACS-1 : MELT-BLOWN POLYPROPYLENE CARTRIDGES

The construction of this pure polypropylene, surfactant-free depth filter ensures low pressure drops, with exceptional dirt holding capabilities. ACS-1 series uses no resin binders, lubricants, antistatic or release agents or other chemical additives. The one-step manufacturing process continuously extrudes and thermally bonds pure polypropylene microfibres into a complex filter matrix. Cartridges are characterized by excellent sediment absorption of sand, silt, rust and suspended solids from potable water.

ACS-1

FCPS, Cartridge for mechanical water treatment



The cartridge made of foamed polypropylene is designed for the mechanical purification of water from sand, dirt and rust. The size of fractions 1 - 100 microns. Recommended for pre-treatment of water.

- Porosity of 1-100 microns
- Standard SlimLine / BB
- Size 5-40 (2 1/2 - 4 1/2) inches
- Operating temperature from +2 to +40 ° C
- The recommended filtration rate is 10-75 l / min.

IMPORTANT: Rinse the filter until the filtered water is clear (at least 2-5 liters). Do not use with water that is microbiologically unsafe or of unknown quality without the necessary disinfection before or after the system. Cartridges are designed to filter only cold drinking water. We recommend regular scheduled maintenance and replacement of the filter cartridge for proper product operation.

Improper use, installation and maintenance may result in property damage or flooding.

Limited Warranty: AQUAFILTER guarantees that this product is free from defects in materials and production.

This limited warranty does not apply to failures caused by misuse, alteration, or non-compliance with instructions for installing or replacing the cartridge.

ACS-1

ФСПС, Картридж для механической очистки воды



Картридж из вспененного полипропилена предназначен для механической очистки воды от песка, грязи и ржавчины. Размер фракций 1 - 100 мкм. Рекомендуется для предварительной очистки воды.

- Пористость 1-100 микрон
- Стандарт SlimLine /BB
- Размер 5- 40 (2 1/2 - 4 1/2) дюймов
- Рабочая температура от +2 до +40 Ос
- Рекомендуемая скорость фильтрации 10-75 л/мин.

ВАЖНАЯ ИНФОРМАЦИЯ: Прополоскайте фильтр, пока фильтрованная вода не станет чистой (не менее 2-5 литров).

Не используйте с водой, которая является микробиологически небезопасной или неизвестного качества без необходимой дезинфекции до или после системы. Картриджи предназначены для фильтрации только холодной питьевой воды. Мы рекомендуем регулярно проводить плановое техобслуживание и замену фильтрующего картриджа для правильной работы продукта.

Неправильное использование, установка и обслуживание могут привести к повреждению имущества или затоплению.

Ограниченная гарантия: AQUAFILTER гарантирует, что этот продукт не имеет дефектов материалов и производства.

Данная ограниченная гарантия не распространяется на сбои, вызванные неправильным использованием, изменением или несоблюдением инструкций по установке или замене картриджа.

CATALOG NUMBER	DESCRIPTION	CONNECTION	SIZE
----------------	-------------	------------	------

FCPS1-5	Melt-blown polypropylene filter cartridge 1 micron	DOE	2 1/2" x 4 7/8"
FCPS5-5	Melt-blown polypropylene filter cartridge 5 micron	DOE	2 1/2" x 4 7/8"
FCPS20-5	Melt-blown polypropylene filter cartridge 20 micron	DOE	2 1/2" x 4 7/8"
FCPS50-5	Melt-blown polypropylene filter cartridge 50 micron	DOE	2 1/2" x 4 7/8"
FCPS1	Melt-blown polypropylene filter cartridge 1 micron	DOE	2 1/2" x 9 7/8"
FCPS5	Melt-blown polypropylene filter cartridge 5 micron	DOE	2 1/2" x 9 7/8"
FCPS10	Melt-blown polypropylene filter cartridge 10 micron	DOE	2 1/2" x 9 7/8"
FCPS20	Melt-blown polypropylene filter cartridge 20 micron	DOE	2 1/2" x 9 7/8"
FCPS50	Melt-blown polypropylene filter cartridge 50 micron	DOE	2 1/2" x 9 7/8"
FCPS1-L	Melt-blown polypropylene filter cartridge 1 micron	DOE	2 1/2" x 20"
FCPS5-L	Melt-blown polypropylene filter cartridge 5 micron	DOE	2 1/2" x 20"
FCPS20-L	Melt-blown polypropylene filter cartridge 20 micron	DOE	2 1/2" x 20"
FCPS50-L	Melt-blown polypropylene filter cartridge 50 micron	DOE	2 1/2" x 20"
FCPS5-30	Melt-blown polypropylene filter cartridge 5 micron	DOE	2 1/2" x 30"
FCPS20-30	Melt-blown polypropylene filter cartridge 20 micron	DOE	2 1/2" x 30"

CATALOG NUMBER	DESCRIPTION	CONNECTION	SIZE
----------------	-------------	------------	------

FCPS5-40	Melt-blown polypropylene filter cartridge 5 micron	DOE	2 1/2" x 40"
FCPS20-40	Melt-blown polypropylene filter cartridge 20 micron	DOE	2 1/2" x 40"
FCPS1M10B	Melt-blown polypropylene filter cartridge 1 micron	DOE	4 1/2" x 9 7/8"
FCPS1M10B	Melt-blown polypropylene filter cartridge 1 micron	DOE	4 1/2" x 9 7/8"
FCPS5M10B	Melt-blown polypropylene filter cartridge 5 micron	DOE	4 1/2" x 9 7/8"
FCPS20M10B	Melt-blown polypropylene filter cartridge 20 micron	DOE	4 1/2" x 9 7/8"
FCPS50M10B	Melt-blown polypropylene filter cartridge 50 micron	DOE	4 1/2" x 9 7/8"
FCPS1M20B	Melt-blown polypropylene filter cartridge 1 micron	DOE	4 1/2" x 20"
FCPS5M20B	Melt-blown polypropylene filter cartridge 5 micron	DOE	4 1/2" x 20"
FCPS20M20B	Melt-blown polypropylene filter cartridge 20 micron	DOE	4 1/2" x 20"
FCPS50M20B	Melt-blown polypropylene filter cartridge 50 micron	DOE	4 1/2" x 20"